


110 m³ Pressure Gas Rail Tank Wagon, ZAGGKS, C-Load Standard Wagon for LPG



A = Length over buffers:	17,900 mm	Tank capacity:	approx. 110 m ³
B = Distance between pivots:	12,000 mm	E = Length over tank bottom:	16,300 mm
C = Axle base in bogie:	1,800 mm	Tank diameter:	3,000 mm
D = Outer axle base:	13,800 mm	Thermal insulation:	Sun shield
Gross vehicle weight:	80 t	Tank material:	e.g. StE47
Tare weight:	approx. 32.2 t	Tank code:	P25BH o. P26BH
Min. track curve radius:	35 m	Calculated temperature:	- 20 /+50°C

Loading limits:

	A	B	C
S	31.8	39.8	47.8

The loading limits are determined according to the measured tare weight and tank volume in litre per wagon!

**110 m³ Pressure Gas Rail Tank Wagon, ZAGGKS, C-Load
Standard Wagon for LPG**Technical Equipment:

Wheel sets:	20.0 t axle load
Draw gear:	draw gear with rubber coated spring
Buffer gear:	sleeve buffer group C, 70 kJ, buffer plate 340 x 450
Brake:	pneumatic brake KE-GP 16“, LL-brake blocks/noise reduced
Filling and discharge device:	Liquid phase: 1 bottom valve DN 80 2 side valves DN 80 Gas phase: 1 bottom valve DN 80 2 side valves DN 50 Operation of bottom valve: combined quick closing aggregate for liquid and gas phase valve, hydraulic, tension cable principle
Couplings:	standard equipment with blind flange Equipment with other coupling systems like WECO or TODO is possible upon customer request.

The rail tank car is registered for the international railway traffic on the European standard gauge.

Aretz type: G110NS-C-UE-S-O-LL-NP-25 or 26